

Location:



SYMMONS® Degas®

Shower System S-5401

Specification Submittal



Feature Highlights

- Symmons Shower System with lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Secondary integral volume control handle
- Showerhead #511SH, one mode, 8-1/2 inch diameter
- Showerhead arm and flange
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available
- Polished chrome finish

Model Numbers

- S-5401
Shower System with Symmons Temptrol® mixing valve
p/n S-46-1-BODY
- S-5401-TRM
Trim only, mixing valve ordered separately
- S-46-1-BODY
Symmons Temptrol® mixing valve without trim
- S-46-1X-BODY
Symmons Temptrol® mixing valve without trim.
Valve includes integral service stops to allow water
shut-off for service



Finish Options / Modifications

Append appropriate -suffix to model number

- STN Satin Nickel
- ORB Oil Rubbed Bronze
- Polished Chrome (standard finish)

Options / Modifications

Append appropriate -suffix to model number

-  -1.5 1.5 gpm (5.7 L/min) flow restrictor
- 2.0 2.0 gpm (7.6 L/min) flow restrictor
- IPS 1/2" female IPS connections
-  -LP Loop handle
- L/HD Less showerhead
- REB Rebuild trim kit, includes TA-10 and TA-4
- REV Reverse coring, hot on right, cold on left, for
back to back installations
- VP Vandal resistant escutcheon screws in place of
standard screws
- X Integral service stops - allows water shutoff at
valve for service
- X-CHKS Integral check stops - for use in installations
where a positive shut-off device is used
downstream of mixing valve

Standards / Certifications

ASME A112.18.1/CSA B125.1



Dimensions Degas Shower System, S-5401

