
Location:



Hand Shower, 522HS Specification Submittal

Model Numbers

☐ 522HS Hand shower: includes wand #412W, flexible metal hose with in-line vacuum breaker, cradle for hand shower, wall connection and flange



Options / Modifications

Append appropriate -suffix to model number.

- -1.5 1.5 gpm (5.7 L/min) flow restrictor
- -2.0 2.0 gpm (7.6 L/min) flow restrictor
 - -QD Quick-disconnect for hand shower
- -LHS Less hand shower wand
 - -R White vinyl hose in place of metal hose
 - -72 6 foot hose in place of 5 foot hose

Feature Highlights

- Three function hand shower with full shower pulsating message and soft shower water saving spray head
- 5 foot flexible metal hose with in-line vacuum breaker
- Hand shower flow rate 2.5 gpm (9.5 L/min)
 Optional lower flow rates
- Polished chrome finish (standard)

Finish Options / Modifications

Append appropriate -suffix to model number.

- ☐ -STN Satin nickel
- ☐ -BBZ Brushed bronze
 - Polished chrome (standard finish)

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime to the original end purchaser in residential / consumer installations
- 5 years for commercial installations

