



**SYMMONS**<sup>®</sup> Symmetrix<sup>®</sup>  
the smart choice<sup>™</sup>

Symmons Symmetrix<sup>®</sup> faucets are available for a wide variety of commercial and institutional applications.

Backed by the legendary Symmons name for quality, you can be assured you are specifying products that deliver the highest performance available in faucet technology, while meeting all known codes and standards.

Beneath the contemporary styling of every Symmons Symmetrix<sup>®</sup> faucet you'll find a heart machined of solid brass and copper. Built to withstand the abuse of time and guaranteed to provide flawless performance under the broadest range of water conditions, our full line of faucets feature the state-of-the-art Symmetrix ceramic control cartridge.



Symmons Symmetrix<sup>®</sup>  
lavatory faucet is  
available in this finish:



Polished  
Chrome

Symmetrix<sup>®</sup> Lavatory Faucets

## Widespread Lavatory Faucets



**S-243-2-LAM**

Two handle lavatory faucet with quarter-turn ceramic control components and lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 8" to 16" centers.

S-243-1-LAM Faucet with lift-rod only

S-243-LAM Faucet only



**S-244-2-LAM**

Two handle lavatory faucet with quarter-turn ceramic control components and lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 8" to 16" centers.

S-244-1-LAM Faucet with lift-rod only

S-244-LAM Faucet only



**S-254-LWG**

Two handle lavatory faucet with quarter-turn ceramic control components and wrist blade lever handles. 9-1/2" rigid/swivel gooseneck spout. Includes aerator. 1/2" IPS shanks, 8" to 16" centers.

**Modifications:** Suffix G: Grid drain in lieu of pop-up (S-244-2 only) • Suffix Delete LAM: Standard blade handles (chrome only) • Suffix FR: .5 GPM flow restrictor outlet spray (vandal resistant) • Suffix LAM: Metal finish insert handles • Suffix LPO: White insert handles • Suffix LWG: Wrist blade handles • Suffix NA: Non-aerated laminar flow outlet spray • Suffix OFG: Offset grid strainer • Suffix VP: Vandal resistant aerator

## Centerset Lavatory Faucets



**S-240-2-LAM**

Two handle lavatory faucet with quarter-turn ceramic control components and blade handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 8" to 16" centers.

S-240-1-LAM Faucet with lift-rod only

S-240-LAM Faucet only



**S-250-2**

Two handle cast brass lavatory faucet with quarter-turn ceramic control components and blade style lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 4" centers.

S-250-1 Faucet with lift-rod only

S-250-0 Faucet without lift-rod hole

S-250 Faucet only



**S-250-2-LWG**

Two handle cast brass lavatory faucet with quarter-turn ceramic control components and wrist blade lever handles. Includes aerator, lift-rod with pop-up drain assembly. 1/2" IPS shanks, 4" centers.

S-250-1-LWG Faucet with lift-rod only

S-250-0-LWG Faucet without lift-rod hole

S-250-LWG Faucet only



**S-20-2**

Single handle lavatory faucet with ceramic control components and handle limit stop. Includes aerator, lift-rod with pop-up drain assembly. 3/8" supplies, 4" centers.

S-20-1 Faucet with lift-rod only

S-20-0 Faucet without lift-rod hole

S-20 Faucet only

S-20-2-G Faucet with grid strainer drain assembly

**Modifications:** Suffix FR: .5 GPM flow restrictor outlet spray (vandal resistant) • Suffix G: Grid drain in lieu of pop-up (S-240-2 only) • Suffix LAM: Metal finish insert handles • Suffix LPO: White insert handles • Suffix LWG: Wrist blade handles • Suffix NA: Non-aerated laminar flow outlet spray • Suffix OFG: Offset grid strainer (S-240-2 only) • Suffix VP: Vandal resistant aerator • Suffix BH: Braided hose supplies • Suffix FR: .5 GPM flow restrictor outlet spray (vandal resistant) • Suffix G: Grid drain in lieu of pop-up (S-240-2 only) • Suffix IPS: 1/2" IPS adaptors • Suffix LP: Loop handle • Suffix W: 6" lever handle (S-20-2 only)