

Reduces Wear on Hoses and Machine

The Laundry-Mate control valve has a unique triple-seal packing and features self-adjusting, spring-loaded, non-wearing action. By eliminating constant water pressure shock, Laundry-Mate extends the life of your washing machine hoses.

Laundry-Mate installs easily between 2" x 4" studs on 16" centers with angle mounting straps (furnished). Copper tubing supplies enter the sides of the unit from above or below and attach to union elbows. Just connect the valve to the union elbows with two screws, install the drain pipe and hoses and screw on the cover – your work is done!



Laundry-Mate® Features

- Easy to install
- Conceals Pipes and Hoses
- Eliminate wheel handle shut-offs
- Flush to wall cover
- Paintable surface
- Easy to read operating
- Plumbing Behind the Wall









Choose Between Two Models

W-600 Laundry-Mate Supply and Drain Fixture for 1/2" copper tubing and 1-1/2" drain

W-602 Laundry-Mate Supply and Drain Fixture for 1/2" copper tubing and 2" drain

Modification:
Suffix X: Service stops in W-600 or W-602
Dimensions:
Box: 8-1/4" x 5-1/2" x 3-3/4" deep
Cover: 9-1/4" x 6-1/2"

Control Valves for Surface Mount Installations

These models are designed for basement areas, unfinished laundry rooms, or remodel work.







W-400 Valve with 1/2" sweat union ell connections

Modifications: Suffix IPSC: 1/2" MIPS or 1/2" sweat connections Suffix IPSF: 1/2" FIPS connections

Other Features of the Symmons® Laundry-Mate®

- Slide action on/off control
- Solid brass drain pan at outlet
- 1-1/2" and 2" drain outlet

- Large metal mounting flanges
- Serviceable/replaceable valve
- Available with service stops

All models feature the original washing machine valve manufactured by Symmons for over 30 years. For protection and assured quality, do not accept substitutes or valves that are not marked Symmons. All hoses and supply pipes shown herein are for illustration purposes only and are not included with the units.

