

Location:

# SYMMONS® Elm™

## Lavatory Faucet SLC-5512 Specifications Submittal



### Model Numbers

- SLC-5512 Centerset Lavatory Faucet with pop-up drain assembly, p/n LN-01642

### Options / Modifications

Append appropriate -suffix to model number

- 0.5 0.5 gpm (1.9 L/min) flow rate restrictor
- 1.0 1.0 gpm (3.8 L/min) flow rate restrictor
- 1.5 1.5 gpm (7.6 L/min) flow rate restrictor
- RB Add red and blue indicators to the handle (Available in chrome only)

### Finish Options / Modifications

Append appropriate -suffix to model number

- STN Satin Nickel
- SBZ Seasoned Bronze
- Polished Chrome (standard finish)

### Feature Highlights

- 4 inch centerset lavatory faucet with lever handles
- Commercial grade 1/4 turn ceramic disc valve cartridge for drip free performance
- Pop-up drain assembly with lift rod
- 1/2 inch IPS shanks
- Standard flow rate is 2.5 gpm (9.5 L/min)  
Optional lower flow rate restrictor available
- Polished chrome finish (standard)

### Standards / Certifications

- ASME A112.18.1-2005 / CSA B125.1-05
- Low lead compliant, AB1953/S.152/S.3874
- WaterSense® Certified
- Americans with Disabilities Act (ADA) compliant

### Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

## Dimensions Elm Centerset Lavatory Faucet, SLC-5512

