Taymor. | P R O D U C T SPECIFICATIONS

FIRE RATED

FIRE RATED

LISTED

Fire rated for 20 minutes

LISTED

Fire rated for 20 minutes

RESIDENTIAL HARDWARE

9/16"

(14 mm)

9/16" (14 mm)

1-3/8" - 2" (35-50 mm)

VISION ANGLE 1/2" (12 mm)

1-3/8" - 2-1/4" (35 - 57 mm)

1/2" (12 mm)

1-3/8" - 2-3/16" (35-55 mm)

9/16

(14 mm)

VISION

ANGLE

11/16"

(18 mm)

-

DOOR VIEWERS/PEEPHOLES





- > 20 MINUTE UL RATED DOOR VIEWER
- > SOLID BRASS
- > BORE SIZE 1/2" (12 mm)
- > ADJUSTABLE FROM 1-3/8" TO 2" (35 mm TO 50 mm)

> 160° FIELD OF VISION

TWO PLASTIC LENSES AND ONE EXTERIOR GLASS LENS
BOX PACK15
SATIN NICKEL26D
SATIN CHROMECASE
PACK160° UL DOOR VIEWER37-P4820SN37-P4820SC25

19/32" (15 mm)

5/8

1-1/32" (27 mm)

(16 mr



160° PEEPHOLE

- BORE SIZE 1/2" (12 mm)
- › ADJUSTABLE FROM 1-3/8" TO 2-1/4" (35 mm TO 57 mm)
- > 160° FIELD OF VISION
- > ZINC DIECAST CONSTRUCTION
- PLASTIC LENSES

BOX PACK	15 SATIN NICKEL	NICKEL	26D SATIN CHROME	CASE PACK
160° DOOR VIEWER	37-P4841SN	37-P4841N	37-P4841SC	25



180° UL PEEPHOLE

- > 20 MINUTE UL RATED DOOR VIEWER
- > SOLID BRASS
- BORE SIZE 9/16" (14 mm)
- › ADJUSTABLE FROM 1-3/8 TO 2" (35 mm TO 50 mm)
- > 180° FIELD OF VISION
- > THREE PLASTIC LENSES AND ONE EXTERIOR GLASS LENS

THREE PERSING EERSES AND ONE EXTENSION GERSS EERS						
DOV DAOY	15	19	26D	CASE PACK		
BOX PACK	SATIN NICKEL	MATTE BLACK	SATIN CHROME	PACK		
180° UL DOOR VIEWER	37-P4825SN	37-P4825BLK	37-P4825SC	25		

