



**CHARACTERISTIC**

- Requires concealed thermostat ref. 5200AE, 5200AE/US and 5200AE/W
- Temperature control knob with security stop at 38°C
- On/off valves (or diverter with stop function) required for each shower function
- Solid brass plate and knob
- ASME : ASME A112.18.1-2011/CSA B125.1-11

**STANDARDS**



**RELATED SKU'S**

- Ref. G00-5100C Extention kit for thermostatic mixing valve - for installation between 80 mm and 125 mm
- Ref. G00-5100G Reinforced stop ring for THG thermostatic with fixing set
- Ref. G00-5200AE/US 3/4" THG thermostat, 60 l/min with wax cartridge, delivered with a built-in box, no trim

**AVAILABLE FINITIONS**

Blush PVD - H62  
 Brass color PVD - H49  
 Brown bronze color PVD - F33  
 Chrome polished - A02  
 Chrome polished / gold polished - G02  
 Gold color PVD - H52

Gold polished - F01  
 Graphite PVD - H64  
 Matt Umber PVD - H67  
 Matt blush PVD - H60  
 Matt brass color PVD - H50  
 Matt brown bronze color PVD - F34

Matt gold color PVD - H53  
 Matt graphite PVD - H65  
 Matt nickel color PVD - H56  
 Nickel color PVD - H55  
 Nickel polished - B01  
 Rose Gold - F27

Silver rhodium - F18  
 Soft gold - F30  
 Soft satin gold - F32  
 Umber PVD - H66