



CHARACTERISTIC

- ASME : ASME A112.18.1-2011/CSA B125.1-11
- DVGW : DW-6512CQ0608

STANDARDS



RELATED SKU'S

- Ref. G00-5100G Reinforced stop ring for THG thermostatic with fixing set
- Ref. G00-5600AE/US 3/4" THG thermostat with wax cartridge, with stop valve and 3 outlets (stop position between outlets), delivered with a built-in box, no trim

AVAILABLE FINITIONS

- | | | | |
|-----------------------|------------------------------------|------------------------------------|---------------------------------------|
| Blush PVD - H62 | Graphite PVD - H64 | Matt gold color PVD - H53 | Polished chrome with gold inlay - GA1 |
| Brass color PVD - H49 | Light coated bronze - D01 | Matt graphite PVD - H65 | Silver polished, antique - H03 |
| Chrome polished - A02 | Matt Umber PVD - H67 | Matt nickel (American satin) - C01 | Soft gold - F30 |
| Gold color PVD - H52 | Matt blush PVD - H60 | Matt nickel color PVD - H56 | Soft matt gold - F31 |
| Gold mat - F07 | Matt brass color PVD - H50 | Nickel color PVD - H55 | Umber PVD - H66 |
| Gold polished - F01 | Matt chrome (American satin) - C02 | Nickel polished - B01 | |