



TZG3-XX-FL/S9, TZG3-XX-FL/S10, TZG3-XX-FL/S12,
TZG13-XX-FL/S9, TZG13-XX-FL/S10, TZG13-XX-FL/S12

SPECIFICATION

- ALUMINUM SHOWER COLUMN CASING
- 6MM THICK TEMPERED GLASS FACING
- ½" THERMOSTATIC VALVE
- 3 FUNCTIONS DIVERTER VALVE WITH HALF ZONES
- ASSEMBLED WITH STAINLESS STEEL BRAIDED HOSES
- SUPPLIED WITH ½" HI-FLOW HOSES
- ANTI-LIMESCALE SILICONE NOZZLES
- PRESSURE : MINIMUM 35 PSI, MAXIMUM 80 PSI
- ½" CONNECTION

AVAILABLE OPTION

- AVAILABLE WITH OR WITHOUT BODY JETS
- CHOICE OF 3 SIZES OF SHOWER HEADS (9",10",12")
- HAND SHOWER HOLDER SUPPORT REPLACED BY A SLIDING BAR

AVAILABLE FINISH

- TEMPERED GLASS: LAMINATED VINYL BACKING FINISHES
REFER TO WEBSITE FOR CHOICE OF COLORS

ACCESSORIES

ACCESSORIES	TZG3-XX-FL/S9	TZG3-XX-FL/S10	TZG3-XX-FL/S12	TZG13-XX-FL/S9	TZG13-XX-FL/S10	TZG13-XX-FL/S12
SHOWER HEAD	PVTS-09-R2	SSTS-10-R	SSTS-12-R	PVTS-09-R2	SSTS-10-R	SSTS-12-R
HAND SHOWER	HS-212	HS-212	HS-212	HS-212	HS-212	HS-212
SUPPORT	HSH-302	HSH-302	HSH-302	HSHC-103-70	HSHC-103-70	HSHC-103-70
HOSE	SSHE-175	SSHE-175	SSHE-175	SSHE-150	SSHE-150	SSHE-150
DIVERTER SPOUT	R-35	R-35	R-35	R-25	R-25	R-25


FLOW RATE

THERMOSTATIC VALVE	30 L/MIN [7.9 GPM] @ 60 PSI
SHOWER HEAD	9.5 L/MIN [2.5 GPM] @ 60 PSI
HAND SHOWER	9.5 L/MIN [2.5 GPM] @ 60 PSI
JETS (2)	9.7 L/MIN [2.6 GPM] @ 60 PSI
DIVERTER SPOUT	17 L/MIN [4.5 GPM] @ 60 PSI
SPOUT	19.7 L/MIN [5.2 GPM] @ 60 PSI

WARRANTY

PRODUCTS COVERED BY A FULL LIMITED LIFETIME WARRANTY AGAINST ALL MANUFACTURING DEFECTS.

FOR MORE INFORMATION ABOUT THE PRODUCT, OR BEFORE PROCEEDING TO ANY INSTALLATION PLEASE CONSULT THE INSTALLATION MANUAL.



THE PRODUCT MAY VARY SLIGHTLY FROM ITS DIMENSION AND APPEARANCE.

REV.: 02/2018