

TZG3-XX-RU/3L, TZG13-XX-RU/3L

SPECIFICATION

- ALUMINUM SHOWER COLUMN CASING
- 6MM THICK TEMPERED GLASS FACING
- SHOWER HEAD WITH LED
- ½" THERMOSTATIC VALVE
- 3 FUNCTIONS DIVERTER VALVE WITH HALF ZONES
- ASSEMBLED WITH STAINLESS STEEL BRAIDED HOSES
- SUPPLIED WITH 1/2" HI-FLOW HOSES
- ANTI-LIMESCALE SILICONE NOZZLES
- Pressure: Minimum 35 psi, maximum 80 psi
- ½" CONNECTION

AVAILABLE OPTION

- AVAILABLE WITH OR WITHOUT BODY JETS
- HAND SHOWER HOLDER SUPPORT REPLACED BY A SLIDING BAR

AVAILABLE FINISH

- TEMPERED GLASS: LAMINATED VINYL BACKING FINISHES

REFER TO WEBSITE FOR CHOICE OF COLORS

ACCESSORIES

ACCESSORIES	TZG3-XX-RU/3L	TZG13-XX-RU/3L
SHOWER HEAD	BJ-13-3L	BJ-13-3L
HAND SHOWER	HS-212	HS-212
SUPPORT	HSH-302	HSHC-103-70
Hose	SSHE-175	SSHE-150
DIVERTER SPOUT	R-35	R-25


FLOW RATE

THERMOSTATIC VALVE	30 L/MIN [7.9 GPM] @ 60 PSI	
Shower head	9.5 L/MIN [2.5 GPM] @ 60 PSI	
HAND SHOWER	9.5 L/MIN [2.5 GPM] @ 60 PSI	
JETS (2)	9.7 L/MIN [2.6 GPM] @ 60 PSI	
DIVERTER SPOUT	17 L/MIN [4.5 GPM] @ 60 PSI	
SPOUT	19.7 L/MIN [5.2 GPM] @ 60 PSI	

WARRANTY

PRODUCTS COVERED BY A FULL LIMITED LIFETIME WARRANTY AGAINST ALL MANUFACTURING DEFECTS. 5-YEAR WARRANTY ON THE LED LIGHTING SYSTEM.

FOR MORE INFORMATION ABOUT THE PRODUCT, OR BEFORE PROCEEDING TO ANY INSTALLATION PLEASE CONSULT THE INSTALLATION MANUAL.



THE PRODUCT MAY VARY SLIGHTLY FROM ITS DIMENSION AND APPEARANCE.

Rev.: 02/2018