

TZST-11.1

SPECIFICATION

- STAINLESS STEEL SHOWER COLUMN, GRADE #304
- ½" THERMOSTATIC VALVE
- 5 SHUT-OFF VALVES WITH VOLUME CONTROL
- ASSEMBLED WITH STAINLESS STEEL BRAIDED HOSES
- SUPPLIED WITH 1/2" HI-FLOW HOSES
- ANTI-LIMESCALE SILICONE NOZZLES
- Pressure: Minimum 35 psi, maximum 80 psi
- ½" CONNECTION

AVAILABLE OPTION

- SHOWER HEAD WITH LED (REF. MODEL TZST-08.1L)
- HAND SHOWER HOLDER SUPPORT REPLACED BY A SLIDING BAR

AVAILABLE FINISH

BRUSHED STAINLESS STEEL: TZST-11.1

ACCESSORIES

| Accessories | TZST-11.1 |
|----------------|-----------|
| SHOWER HEAD | BJ-11.1 |
| HAND SHOWER | HS-203 |
| SUPPORT | HSH-302 |
| Hose | SSHE-175 |
| DIVERTER SPOUT | R-36 |


FLOW RATE

| THERMOSTATIC VALVE | 30 L/міn [7.9 gpм] @ 60 psi |
|--------------------|-------------------------------|
| Shower head | 9.5 L/мін [2.5 gpм] @ 60 psi |
| HAND SHOWER | 9.5 L/мін [2.5 gpм] @ 60 psi |
| JETS (3) | 10.9 L/MIN [2.9 GPM] @ 60 PSI |
| DIVERTER SPOUT | 17 L/MIN [4.5 GPM] @ 60 PSI |
| SPOUT | 19.7 L/MIN [5.2 GPM] @ 60 PSI |

WARRANTY

PRODUCTS COVERED BY A FULL LIMITED LIFETIME WARRANTY AGAINST ALL MANUFACTURING DEFECTS.

FOR MORE INFORMATION ABOUT THE PRODUCT, OR BEFORE PROCEEDING TO ANY INSTALLATION PLEASE CONSULT THE INSTALLATION MANUAL.



THE PRODUCT MAY VARY SLIGHTLY FROM ITS DIMENSION AND APPEARANCE.

Rev.: 02/2018