

TZST-13, TZSTC-13, TZSTBL-13, TZST-13/B36, TZSTC-13/B36, TZSTBL-13/B36

SPECIFICATION

- STAINLESS STEEL SHOWER COLUMN, GRADE #304
- ½" THERMOSTATIC VALVE
- 3 FUNCTIONS DIVERTER VALVE WITH HALF ZONES
- ASSEMBLED WITH STAINLESS STEEL BRAIDED HOSES
- SUPPLIED WITH 1/2" HI-FLOW HOSES
- ANTI-LIMESCALE SILICONE NOZZLES
- Pressure: Minimum 35 psi, maximum 80 psi
- ½" CONNECTION

AVAILABLE OPTION

- SHOWER HEAD WITH LED (REF. MODEL TZST-13L)
- ADDITION OF A DIVERTER SPOUT (REF. MODEL TZST-13/B36)
- HAND SHOWER HOLDER SUPPORT REPLACED BY A SLIDING BAR

AVAILABLE FINISH

- BRUSHED STAINLESS STEEL: TZST-13

- MIRROR BLACK: TZSTBL-13

- CHROME: TZSTC-13

ACCESSORIES

Accessories	TZST-13	TZSTC-13	TZSTBL-13	TZST-13/B36	TZSTC-13/B36	TZSTBL-13/B36
SHOWER HEAD	BJ-13	BJ-13	BJ-13	BJ-13	BJ-13	BJ-13
HAND SHOWER	HS-204	HS-204	HS-204	HS-204	HS-204	HS-204
SUPPORT	HSHC-101	HSHC-101	HSHC-101	HSH-302	HSH-302	HSH-302
HOSE	SSHE-125	SSHE-125	SSHE-125	SSHE-175	SSHE-175	SSHE-175
DIVERTER SPOUT	N/A	N/A	N/A	R-36	R-36	R-36


FLOW RATE

THERMOSTATIC VALVE	30 L/MIN [7.9 GPM] @ 60 PSI		
Shower head	9.5 L/MIN [2.5 GPM] @ 60 PSI		
HAND SHOWER	9.5 L/MIN [2.5 GPM] @ 60 PSI		
JETS (2)	9.7 L/MIN [2.6 GPM] @ 60 PSI		
DIVERTER SPOUT	17 L/MIN [4.5 GPM] @ 60 PSI		
Spout	19.7 L/MIN [5.2 GPM] @ 60 PSI		

WARRANTY

PRODUCTS COVERED BY A FULL LIMITED LIFETIME WARRANTY AGAINST ALL MANUFACTURING DEFECTS.

FOR MORE INFORMATION ABOUT THE PRODUCT, OR BEFORE PROCEEDING TO ANY INSTALLATION PLEASE CONSULT THE INSTALLATION MANUAL.



THE PRODUCT MAY VARY SLIGHTLY FROM ITS DIMENSION AND APPEARANCE.

Rev.: 02/2018