

Modern Series Aero Rain Shower

FEATURES

- Air injected AeroJet+ Technology
- 2.0 gpm (7.5 lpm) maximum flow rate
- 8" diameter spray face
- Rubber nozzles to prevent limescale build up

COLORS/FINISHES

- #CP Polished Chrome
- #BN Brushed Nickel
- #PN Polished Nickel



CODES/STANDARDS

- Meets or exceeds ASME A112.18.1/CSA B125.1
- Certifications: IAPMO(cUPC), State of Massachusetts and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



PRODUCT SPECIFICATION

The shower shall have air injected AeroJet+ technology. Product shall have 2.0 gpm (7.5 lpm) max. flow rate. Product shall have 8" diameter spray face. Product shall have rubber nozzles to prevent limescale build up. Product shall be **TOTO Model TS111BL8#_____**.

Please note the following components are sold separately:



TS110MV16
Shower Arm Wall
Mount



TS110MC6
Shower Arm Ceiling
Mount

TS111BL8



Modern Series Aero Rain Shower

SPECIFICATIONS


- Warranty: Lifetime Limited Warranty (Residential Use)
One Year (Commercial Use)
- Material: Brass
- Shipping Weight: 4.3 lbs.
- Shipping Dimensions: 13-1/8" x 14-1/8" x 4-1/4"
- Maximum Flow Rate: 2.0 gpm (7.5 lpm)

INSTALLATION NOTES

- Required Components:
- TS110MV16 (Wall Mount Shower Arm)
 - TS110MC6 (Ceiling Mount Shower Arm)



Shown with
TS110MV16



Shown with
TS110MC6

TOTO

These dimensions and specifications are subject to change without notice