



ECHO

EC130-XX

SPECIFICATION

- Made of solid brass (Lead-free)
- Ceramic cartridge
- Swivel pull down hand spray
- 2 functions spray head
- 3/8" female connections
- 24" Nylon/PEX Hoses
- Flow rate: 6.6L/min [1.75 gpm] @60psi
- Flow rate: 5.7L/min [1.50 gpm] @60psi (LEED)
- Cartridge: CAR-GN-SL35-01
- Limited lifetime warranty

AVAILABLE FINISHES

- Refer to the catalog for available finishes

CERTIFICATION

- ASME 112.18.1 / CSA B125.1



For more information about the product of before proceeding to any installation please consult the guide.
Products covered by a limited lifetime warranty against all manufacturing defects.

SPÉCIFICATION

- Fabriqué de laiton massif
- Cartouche en céramique
- Douchette rétractable a 2 jets
- Connexion 3/8" femelle
- Boyaux d'alimentation Nylon/PEX de 24"
- Débit: 6.6L/min [1.75 gpm] @60psi
- Débit: 5.7L/min [1.50 gpm] @60psi (LEED)
- Cartouche: CAR-GN-SL35-01
- Garantie à vie limitée

FINIS DISPONIBLE

- Se référer au catalogu

CERTIFICATION

- ASME 112.18.1 / CSA B125.1



Pour plus d'information sur le produit ou avant de procéder à toute installation veuillez consulter le guide.
Produits couverts par une garantie à vie limitée contre tout défaut de fabrication.

