


ASSEMBLY INSTRUCTIONS



Sarnen Small Flush Mount

Item # ARN4355

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver

Slotted Screwdriver


1. Carefully remove all parts from the box. Place on a clean, soft surface.
 2. Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)**.
 3. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut **(A)**.
- NOTE:** It is imperative that the fixture is grounded.
4. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut **(A)**.
 5. Connect fixture hot wire (black) to the supply hot wire (usually black) using wire nut **(A)**.

CAUTION: Do not reverse the hot and neutral connections.

6. Make sure all wire connections are tight, then carefully tuck into the junction box.
7. Route all wires through the shade **(D)**, then install shade **(D)** to mounting plate **(B)** and secure with lock washer **(F)** and hex nut **(E)** using provided wrench **(J)**.
8. Connect fixture ground wire (bare copper) to the socket ground wire (bare copper) using wire nut **(A)**.

NOTE: It is imperative that the fixture is grounded.

ASSEMBLY INSTRUCTIONS



Sarnen Small Flush Mount

Item # ARN4355

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

9. Connect fixture neutral wire (white) to the socket neutral wire (usually white) using wire nut **(A)**.
10. Connect fixture hot wire (black) to the socket hot wire (usually black) using wire nut **(A)**.

CAUTION: Do not reverse the hot and neutral connections.

11. Install socket **(G)** to shade **(D)** and secure with the threaded caps **(H)**.

12. Install light bulb into the socket.

13. Thread shade **(I)** to socket.

NOTE: Do not overtighten otherwise glass shade could be damaged.

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.