


ASSEMBLY INSTRUCTIONS



Kelley Large Chandelier

Item # NW5070

NOTICE:


This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver	Slotted Screwdriver	Wire Strippers
Slip Joint Pliers	Measuring Tape	Chain Pliers
Wire Cutters		

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. It is recommended to install a 1/4 IPS threaded pipe, secured to a structural member of the building. Then install threaded nipple (**B**) into receiver and tighten with wrench.
NOTE: Item must be supported independent of the junction box due to hanging weight.
3. Install lock collar (**C**) to threaded receiver attached to structural member by tightening locknut.
4. Install shade (**H**) split washer above knurled ring (**I**) and secure by screwing tight.
5. Feed electrical wires through bottom rod (**G**) and connect to fixture body (**J**).
6. Continue feeding wires through collar ring (**E**), canopy (**D**) and top rod (**F**).
7. Holding fixture upright, slide collar ring (**E**) and canopy (**D**) down and rest on rod (**G**). Then connect top rod (**F**) to middle rod (**G**).
NOTE: Slide components down slowly to avoid damage.
8. Install entire fixture by thread top rod (**F**) to collar loop (**C**).

ASSEMBLY INSTRUCTIONS



Kelley Large Chandelier

Item # NW5070

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

9. Cut excess wires, being sure to leave enough to reach the junction box. Separate wires and strip insulation on each 5/8".
 10. Loosen cable lock and install to end of safety cable. Run safety cable through junction box and around structural member of building. Insert cable through cable lock and tighten the ends with a screwdriver to secure (see diagram 1).
 11. Connect fixture ground wire (bare copper) to the supply ground wire (usually green or bare copper) using wire nut **(A)**.
- NOTE:** It is imperative that the fixture is grounded.
12. Connect fixture neutral wire (ribbed) to the supply neutral wire (usually white) using wire nut **(A)**.
 13. Connect fixture hot wire (smooth with markings) to the supply hot wire (usually black) using wire nut **(A)**.
- CAUTION:** Do not reverse the hot and neutral connections.
14. Make sure all wire connections are tight, then carefully tuck into the junction box.
 15. Install canopy **(D)** to collar loop **(C)** and secure with collar ring **(E)**.
 16. Clip shades **(K)** onto light bulbs.

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.