


ASSEMBLY INSTRUCTIONS



Casoria Medium Two-Tier Chandelier

Item # ARN5483

NOTICE:


This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver	Slotted Screwdriver	Wire Strippers
Slip Joint Pliers	Measuring Tape	Chain Pliers
Wire Cutters		

- Carefully remove all parts from the box. Place on a clean, soft surface.
- Remove collar loop **(D)** from chain **(G)** by unscrewing quick link **(H)**.
- Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)**.
- Secure collar loop **(D)** to mounting plate **(B)** using pliers to tighten locknut.
- Install canopy **(E)** to collar loop **(D)** and secure with collar ring **(F)**.
- Install threaded tube **(S)** to hickey **(Q)** using pliers to tighten locknut.
- Feed the fixture wires from fixture body **(J2)** through tube **(R)** and rest tube **(R)** on the top of fixture body **(J2)**.
- Connect corresponding neutral wire (white) from fixture body **(J1)** and fixture body **(J2)** using wire nut **(U)**.
- Connect corresponding hot wire (black) from fixture body **(J1)** and fixture body **(J2)** using wire nut **(U)**.
- Install fixture body **(J2)** to threaded tube **(S)** and secure with metal washer **(T)** and hex nut **(V)** using provided wrench.

ASSEMBLY INSTRUCTIONS



Casoria Medium Two-Tier Chandelier


Item # ARN5483

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

11. Feed fixture wire and ground wire through tube **(P)** and connect tube **(P)** to fixture body **(J1)**.
12. Thread finial **(O)** to the bottom of fixture body **(J2)**.
13. Determine desired overall length, and amount of chain **(G)** needed. Shorten chain using chain pliers. (Keep extra chain)
14. Attach chain **(G)** to collar loop **(D)** and to fixture loop **(I)** using quick links **(H)**. Secure quick links **(H)**.
15. Thread fixture wire and ground wire through chain **(G)**.
NOTE: When you reach the collar loop **(D)**, ensure there is no tension on the wires. Cut excess wires, being sure to leave enough to reach the junction box.
16. Separate two sides of molded wire, and strip insulation on each 5/8".
17. Loosen collar ring **(F)** and let canopy **(E)** slip down chain **(G)** carefully.
18. Twist all fixture wires together, and slip through center hole of collar loop **(D)**.
NOTE: Untwist wires and separate to prepare for connection.
19. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut **(A)**.
NOTE: It is imperative that the fixture is grounded.

ASSEMBLY INSTRUCTIONS



Casoria Medium Two-Tier Chandelier

Item # ARN5483

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

20. Connect fixture neutral wire (ribbed) to the supply neutral wire (usually white) using wire nut **(A)**.
21. Connect fixture hot wire (smooth with markings) to the supply hot wire (usually black) using wire nut **(A)**.
CAUTION: Do not reverse the hot and neutral connections.
22. Make sure all wire connections are tight, then carefully tuck into the junction box.
23. Install canopy **(E)** to collar loop **(D)** and secure with collar ring **(F)**.
24. Install light bulbs into the sockets.
25. Attach glass panels **(L)** and rubber washers **(K)** to socket cup and secure with screws **(M)**.
NOTE: Do not overtighten otherwise glass could become damaged.

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.