


ASSEMBLY INSTRUCTIONS



Go Lightly Small Chandelier

Item # BBL5080

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver	Slotted Screwdriver	Wire Strippers
Slip Joint Pliers	Measuring Tape	Chain Pliers
Wire Cutters		


1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Install mounting plate **(A)** to junction box and secure with mounting screws **(B)**.
3. Install canopy **(C)** to rod **(E)** and secure with hex nut **(D)**.
4. Determine desired overall length, and amount of chain **(F)** needed. Shorten chain using chain pliers. (Keep extra chain)
5. Attach chain **(F)** to loop **(D)** on bottom of rod **(F)** and to fixture loop **(G)** using quick links **(J)**. Secure quick links **(J)**.
6. Thread fixture wire and ground wire through chain **(F)** and rod **(E)**.

NOTE: When you reach the loop **(K)**, ensure there is no tension on the wires. Cut excess wires, being sure to leave enough to reach the junction box.

7. Separate two sides of molded wire, and strip insulation on each 5/8".
8. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut **(I)**.

NOTE: It is imperative that the fixture is grounded.

ASSEMBLY INSTRUCTIONS



Go Lightly Small Chandelier

Item # BBL5080

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

9. Connect fixture neutral wire (ribbed) to the supply neutral wire (usually white) using wire nut **(I)**.
10. Connect fixture hot wire (smooth with markings) to the supply hot wire (usually black) using wire nut **(I)**.

CAUTION: Do not reverse the hot and neutral connections.

11. Make sure all wire connections are tight, then carefully tuck into the junction box.

12. Thread rod **(E)** to mounting plate **(A)**.

13. Place shades **(H)** onto socket cups.

NOTE: If shade has additional packaging, carefully cut from interior of shade to avoid damage.

14. Install light bulbs into the sockets.

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.