


ASSEMBLY INSTRUCTIONS



Barrett 21" Up and Down Bath Light

Item # RL2116

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):


Phillips Screwdriver

Slotted Screwdriver

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove mounting plate **(B)** from fixture **(E)** by removing screws **(D)**.
3. Connect filter **(K)** input neutral wire (white) to the supply neutral wire (usually white) using wire nut **(A)**.
4. Connect filter **(K)** input hot wire (black) to the supply hot wire (usually black) using wire nut **(A)**.
CAUTION: Do not reverse the hot and neutral connections.
5. Insert filter **(K)** and driver **(F)** into junction box.
6. Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)**.
7. Connect supply ground wire (usually green or bare copper) and filter **(K)** ground wire (yellow and green) around the green grounding screw (see diagram 1). Tighten.
NOTE: It is imperative that the fixture is grounded.
8. Connect quick connector **(G1 & G2)** together.
9. Make sure all wire connections are tight, then carefully tuck into the junction box.
10. Install fixture **(E)** to mounting plate **(B)** and secure with screws **(D)**.

RALPH LAUREN

ASSEMBLY INSTRUCTIONS



Barrett 21" Up and Down Bath Light

Item # RL2116

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

11. Remove protective caps **(J)** from light source bases (see diagram 2), then thread light sources **(I)** to light source bases.

NOTE: Discard protective caps **(G)** after assembly.

12. Thread glass shades **(H)** to fixture **(E)**.

NOTE: Do not overtighten otherwise shade could become damaged.

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.

RALPH LAUREN