

Toilet seat Architectura

Model ——	9M83U1 Architectura toilet seat with Soft Closing and Quick Release, incl. hinge 9224 17 61	
Product Description ——	Architectura toilet seat in Wrap Over design made of colour ingrained duroplast	
	 incl. hinge in stainless steel and nylon centre distance: 7 0/10" (180 mm) load of ring seat: 529,10lbs (240 kg) 1 year guarantee 	19,17 " (487 mm)
Colour Programme ——] 01 White	
Hinge Finish ——	61 Stainless steel	•
Spare parts ——	 A) 9224 17 61 Hinge in stainless steel and nylon B) 9219 48 00 Buffer for seat and cover C) 9221 18 00 Soft Closing packet 	A
Cleaning Instructions ——	 This toilet seat has been designed and manufactured with great care and attention to detail. If you follow a few simple cleaning instructions you will be able to enjoy its comfort, quality and beauty every day: In order to ensure the best possible hygiene the surface of the toilet seat is closed and pore-free. Please do not use abrasive, corrosive or chlorine based cleaners as these may lead to discoloration and flash rust. Please only use mild ph neutral soap for cleaning. If seat and cover make contact with toilet cleaners and or other aggressive cleaners, please immediately rinse with pure water. 	A CHICO
	 After cleaning please dry off any residual dampness with a soft cloth. Seat and cover must be left in an upright position until all cleaning agents in the bowl has been flushed away. 	
Material Description ——	 TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic compromises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains < 0.03% free formaldehyde and even less following curing. BUFFERS: PE (Polyethylene) DAMPER KIT: Hydraulic damper with stainless steel damper casing and plastic parts DAMPER LIQUID: Anti-friction liquid HINGES: Staipless steel and pylon 	e e
	 DAMPER LIQUID: Anti-friction liquid HINGES: Stainless steel and nylon 	



٦Ũ

С

_ 14,82*"* (402 mm)

9,13" (232 mm)

> 12,99" (330 mm)

_____16,38" (416 mm) 19,45 " (494 mm)

Villeroy & Boch AG PO box 11 20 66688 Mettlach Germany

www.villerov-boch.com

Service contact: E-mail.: inquiries@villeroy-boch-usa.com Tel.: TOTO USA 888-295-8134