

Subway - Wall-mounted toilet with rimless flushing (DirectFlush) - 1.6/0.8 gpf (6/3 lpf)

Features

- Wall-mounted toilet with rimless flushing (DirectFlush)
- 16 1/8" x 22 7/8" (410 x 580 mm)
- 1.6/0.8 gpf (6/3 lpf)
- Washdown model
- Rear outlet
- Concealed trapway
- D-shape bowl

The bowl is to be used with In-wall tank/carrier from TOTO (WT152M DUOFIT IN-WALL TANK SYSTEM) or Geberit (# 111.335.00.5) to satisfy EPA WaterSense.

Optional CeramicPlus - CeramicPlus is a particularly easy-care and dirt-repellent surface. With ceramicplus water immediately forms droplets that simply flow off the surface, taking the dissolved dirt and limescale with them.



Codes / Standard applicable

- ADA compliant
- EPA - Watersense
- Meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14
- Certifications: IAPMO(cUPC), State of Massachusetts
- Code Compliance: UPC, IPC, NSPC, NPC Canada and others



Colors - XX

- 01 = White Alpin
- R1 = White Alpin CeramicPlus

Product Specification

This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22 7/8" (580mm) x 16 1/8" (410mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 4609UR.

Components

Included	
4609 UR XX	Wall-mounted toilet with rimless flushing (DirectFlush)
9222 63 00	Fixation set SupraFix Compact
Required	
9M82 U1 01	WC-seat and cover Comfort

Installation Notes

Install this product according to the installation manual.

Proper wall construction is required for best support of wall mounted toilets. V & B recommends the use of 3/4" greenboard (minimum thickness), instead of drywall, for wall area where toilet will be installed. Ceramic tile is recommended for finishing the surface.

Both the greenboard and ceramic tile must be properly sealed against wet conditions.

Technical Information

Water use	1.6/0.8 gpf (6/3 lpf)
Material	Vitreous china
Warranty	One year limited warranty
Min Water pressure	8 psi
Water surface	4" x 5" (100 x 130 mm)
Trap diameter	2 1/8" (51mm)
Trap seal	2 1/4" (55mm)
Minimum rough-in	7" (180 mm) rough-in
Outlet	Rear outlet

Technical Drawing

