5600 U0 XX



Subway - Wall-mounted toilet - sleek - 1.6/0.8 gpf (6/3 lpf)

Features

- Wall-mounted toilet sleek
- 14 3/4" x 22 1/4" (375 x 565 mm)
- 1.6/0.8 gpf (6/3 lpf)
- · Washdown model
- Rear outlet
- Concealed trapway
- D-shape bowl

Optional CeramicPlus - CeramicPlus is a particularly easy-care and dirtrepellent surface. With ceramicplus water immedialtely forms droplets that simply flow off the surface, taking the dissolved dirt and limescale with them.





Codes / Standard applicable

- Meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14
- Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada and others
- EPA Watersense







Product Specification

This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22 1/4" (565mm) x 14 3/4" (375mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5600U0.

Components

Included	
5600 U0 XX	Wall-mounted toilet - sleek
Required	
9M68 U1 01	WC-seat and cover
9M68 U0 01	WC-seat and cover

• 01 = White Alpin

• R1 = White Alpin CeramicPlus



Installation Notes

Install this product according to the installation manual.

Proper wall construction is required for best support of wall mounted toilets. V&B recommends the use of 3/4" greenboard (minimum thickness), instead of drywall, for wall area where toilet will be installed. Ceramic tile is recommended for finishing the surface. Both the greenboard and ceramic tile must be properly sealed against wet conditions.

Technical Information

Water use 1.6/0.8 gpf (6/3 lpf) Material Vitreous china Warranty One year limited warranty Min Water pressure 8 psi

4" x 5 1/5" (104 x 132 mm) Water surface

Trap diameter 2 1/8" (51mm) 2 1/4" (55mm) 7" (180 mm) rough-in Trap seal Minimum rough-in

Outlet Rear outlet

Shipping dimensions 22 1/4" x 14 3/4" (565 x 375 mm)

66.12 lbs (29.99 kg) Shipping weight Net weight 57.32 lbs (26 kg)

Technical Drawing





