6610 U1 XX

Villeroy & Boch

Subway - 2-PC toilet - 1.6/0.8 gpf (6/3 lpf)

Features

- 2-PC toilet
- 14 5/8" x 31 7/8" x 26 3/8" (370 x 810 x 670 mm)
- 1.6/0.8 gpf (6/3 lpf)
- · Washdown model
- Vario drain Bend (use except with wax ring)
- Concealed trapway
- D-shape bowl

Optional CeramicPlus - CeramicPlus is a particularly easy-care and dirtrepellent surface. with ceramicplus water immedialtely forms droplets that simply flow off the surface, taking the dissolved dirt and limescale with them.



Codes / Standard applicable

- Meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14
- Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others
- · Code Compliance: UPC, IPC, NSPC, NPC Canada and others
- · EPA Watersense







Colors - XX

- 01 = White Alpin
- R1 = White Alpin CeramicPlus

Product Specification

This two-piece toilet is made of vitreous china. The two-piece toilet is $27 \, 3/8$ " (680mm) x 14 5/8" (370mm) x 31 7/8" (810mm). The product has a concealed trapway and a D-shape bowl. The product is available with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The two-piece toilet is Villeroy & Boch model 6610U1.

Components

Included	
6610 U1 XX	2-PC toilet, includes "Vario Drainbend" for vertical outlet installation, Incl. fastening set for concealed mounting system
8701 20 00	Vario drainbend
Required	
7723 U1 XX	Tank, Standard bottom inlet, dual-flush 1.6/0.8 gpf, push button in chrome finish, in chrome
9M55 U1 01	WC-seat and cover, with QuickRelease and SoftClosing toogle hinges in stainless steel
98M9 U1 01	WC-seat and cover, with QuickRelease and SoftClosing hinges in stainless steel
98M9 U0 01	WC-seat and cover, Hinges in stainless steel

Villeroy & Boch

Installation Notes

Install this product according to the installation manual.

Technical Information

Water use 1.6/0.8 gpf (6/3 lpf) Material Vitreous china

Warranty One year limited warranty

Min Water pressure

8 psi 4" x 5" (104 x 129mm) Water surface 2 1/8" (51mm) 2 1/4" (55mm) Trap diameter Trap seal 12" (305 mm) rough-in Minimum rough-in


Outlet Vario drain Bend (use except with wax

27 1/6" x 17 1/8" x 15 1/6" (690 x 435 x Shipping dimensions

385 mm)

Shipping weight 83.37 lbs (37.81 kg) 80.47 lbs (36.5 kg) Net weight

Technical Drawing



See typical Floor mount water closet rough - in drawing

