

R2FSAL

2" FQ - Square Adjustable Trimless



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 0-35° vertical tilting Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction:	Durable die-cast aluminum construction
Input	Universal 120-277V AC 50/60 Hz
Dimming:	Electronic Low Voltage (ELV): 100%-1% Triac: 100%-1% 0-10V: 100-1%
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accommodates 1/2" - 1" ceiling thickness
Finish:	Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
Standards:	ETL & cETL Damp Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant.

Model	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R2FSAL <i>Square Trimless</i>	N 25°	1745	4490	927 2700K	90	BK DB HZ WT	<i>Black</i> <i>Dark Bronze</i> <i>Haze</i> <i>White</i>
		F 40°	1725	2920				
		W 55°	1740	2200				
		N 25°	1835	4725	930 3000K	90		
		F 40°	1820	3075				
		W 55°	1830	2315				

R2FSAL-__-__

Example: **R2FSAL-927-WT** (Beam N-25° reflector is pre-installed. Beams F-40° and W-55° reflectors are included.)

* Lumens and CBCP are reference values for 3000K trim with **3** housing. Use multiplier table below to determine the output for other combinations.

Multiplier		TRIM	
		927	930
HOUSING	3	0.95	1.00
	2	0.83	0.87
	1	0.61	0.64

Example: **R2FSAL-930-WT** N-25° beam in **1** housing: 1835 lm (Reference Output) x 0.64 (Multiplier) = 1175 lm
4725 CBCP (Reference Output) x 0.64 (Multiplier) = 3025 CBCP

Please see next page for housing units (required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760


R2FSAL

2" FQ - Square Adjustable Trimless

WAC LIGHTING

HOUSING (Required)

New Construction
IC Airtight



Model

Power

Emergency Backup

R2FSNL

1 15W IC
2 21W IC
3 25W Non-IC

N/A

R2FS ____ - ____

Example: R2FSNL-3

GLARE CONTROL ACCESSORIES

LENS-11-HCM	Honeycomb Louver
LENS-11P-CRL-BK	Cross Louver

LENS ACCESSORIES

LENS-11	AMB RED BLU GRN SPR BEL	Amber Red Blue Green Spread Beam Elongating
---------	--	--

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760