

R2FSDT-WD

2" FQ - Square Downlight Trim (Dim-To-Warm)

WAC LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION


The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 30° shielding angle design for better visual comfort
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction:	Durable die-cast aluminum construction
Input	Universal 120-277V AC 50/60 Hz
Dimming:	Electronic Low Voltage (ELV): 100%-1% Triac: 100%-1% 0-10V: 100-1%
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accommodates 1/2" - 1" ceiling thickness
Finish:	Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
Standards:	ETL & cETL Wet Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R2FSDT Square Trim	F 40°	1040	1710	WD 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
		W 55°	1020	1240				

R2FSDT-WD-__

Example: **R2FSDT-WD-BK** (Beam F-40° reflector is pre-installed. Beam W-55° reflector is included.)

Please see next page for housing units (required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760


R2FSDT-WD

2" FQ - Square Downlight Trim (Dim-To-Warm)

WAC LIGHTING

HOUSING (Required)

New Construction IC Airtight



Model

Power


Emergency Backup

R2FBNT

1 15W IC

EM *Optional*

New Construction Frame-in Non-IC




R2FBFT

1 15W Non-IC

EM *Optional*

Remodel Non-IC




R2FBRT

1 15W Non-IC

N/A

Remodel IC



R2FBR2T

1 15W IC

N/A

R2FB ____ - ____

Example: **R2FBNT-1** or **R2FBNT-1-EM** (with Emergency backup battery)

GLARE CONTROL ACCESSORIES

LENS-11-HCM
LENS-11P-CRL-BK

Honeycomb Louver
Cross Louver

LENS ACCESSORIES

LENS-11

AMB
RED
BLU
GRN
SPR
BEL

Amber
Red
Blue
Green
Spread
Beam Elongating

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760