

R4FSAT-WD

4" FQ - Square Adjustable Trim (Dim-To-Warm)

WAC LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 0-45° vertical tilting and 365° horizontal rotation
- Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction:	Durable die-cast aluminum construction
Input	Universal 120-277V AC 50/60 Hz
Dimming:	Electronic Low Voltage (ELV): 100%-1% Triac: 100%-1% 0-10V: 100-1%
Light Source:	High output 3-step Mac Adam Ellipse COB Rated life of 50,000 hours at L70
Mounting:	Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accommodates 1/2" - 1" ceiling thickness
Finish:	Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
Standards:	ETL & cETL Damp Location Listed, Title 24 JA8-2019 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R4FSAT Square Trim	F 30°	910	2945	WD 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
		W 50°	890	1740				

R4FSAT-WD-__

Example: **R4FSAT-WD-BK** (Beam F-30° reflector is pre-installed. Beam W-50° reflector is included.)

*Lumens and CBCP are reference values for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

Multiplier		TRIM
HOUSING	2	1.00
	1	0.69

Example: **R4FSAT-WD-WT** with F-30° beam in 1 housing: 910 lm (Reference Output) x 0.69 (Multiplier) = 630 lm
2945 CBCP (Reference Output) x 0.69 (Multiplier) = 2035 CBCP

Please see next page for housing units (required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

R4FSAT-WD

4" FQ - Square Adjustable Trim (Dim-To-Warm)

WAC LIGHTING

HOUSING (Required)		Model	Power	Emergency Backup
New Construction IC Airtight		R4FBNT	1 13W IC 2 19W IC	EM Optional
New Construction Frame-in Non-IC		R4FBFT	1 13W Non-IC 2 19W Non-IC	EM Optional
Remodel Non-IC		R4FBRT	1 13W Non-IC 2 19W Non-IC	N/A

R4FB__ - __

Example: **R4FBNT-2** or **R4FBNT-2-EM** (with Emergency backup battery)

GLARE CONTROL ACCESSORIES

LENS-16-HCM	Honeycomb Louver
LENS-16P-CRL-BK	Cross Louver

LENS ACCESSORIES

LENS-16	AMB RED BLU GRN SPR BEL	Amber Red Blue Green Spread Beam Elongating
---------	--	--

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760