

WAC LIGHTING

Nest

Outdoor Wall Sconce 3000K

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-W26712 12"	3000K 90	BZ Bronze	8.5W	180	145

Example: **WS-W26712-BZ**

For custom requests please contact customs@waclighting.com

DESCRIPTION

A harmonious blend of arts and crafts. Nest is constructed with extruded aluminum louvers to create a dramatic pattern of illumination. The frame is solid die-cast aluminum with weather resistance and a powder coated finish. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Extruded aluminum louvers create a dramatic pattern of light to generate interest
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	54000 Hours
Standards:	ETL, cETL, IP65, Dark Sky Friendly Wet Location Listed
Construction:	Aluminum hardware with glass diffuser

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



FINISHES:



Bronze

LINE DRAWING:

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Nest

Outdoor Wall Sconce 3000K

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-W26716 16"	3000K 90	BZ Bronze	13W	280	210

Example: **WS-W26716-BZ**

For custom requests please contact customs@waclighting.com

DESCRIPTION

A harmonious blend of arts and crafts. Nest is constructed with extruded aluminum louvers to create a dramatic pattern of illumination. The frame is solid die-cast aluminum with weather resistance and a powder coated finish. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Extruded aluminum louvers create a dramatic pattern of light to generate interest
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	54000 Hours
Standards:	ETL, cETL, IP65, Dark Sky Friendly Wet Location Listed
Construction:	Aluminum hardware with glass diffuser



FINISHES:



Bronze

LINE DRAWING:

