



MODEL

DESCRIPTION

3M RO401
Reverse Osmosis
Water Filter System

Part # WI-3MRO401

The 401 RO system by 3M is an advanced four-stage system. Includes an airgap faucet*, install kit, feed water adaptor, tubing and storage tank.

Reduction Claims:

Particulate (5 micron rating) • CTO (Chlorine Taste & Odor) • Arsenic • Barium • Cadmium • Chromium
Copper • Cyst • Fluoride • Lead • Radium • Selenium • TDS (Total Dissolved Solids) • Turbidity
THE 401 MODEL HAS THESE ADDITIONAL CLAIMS: Arsenic (Pentavalent) • Chromium Hex & Chromium Tri
Select VOC's • Toxaphene • p-Dichlorobenzene



Production: 23.92 gallons per day (90.55 liters)

Product Features:

- Installs under the sink for dedicated drinking and cooking water use.
- 5 micron sediment/carbon pre-filter for optimal sediment holding capacity.
- **10 micron nominal carbon block post-filter to provide satisfying flow from faucet.** (R0401&501 upgrade)
- Sanitary quick change (SQC) design: fast and easy 1/4 turn replacement filter change-outs without the need of a filter wrench.
- System designed for both chlorinated and non-chlorinated municipal or well systems.
- Auto shut off helps conserve water (compared to systems without an auto shut off): system shuts down when storage tank is full and automatically turns on to refill tank.
- No electricity required • Clearer ice cubes
- NSF Certified for Standard 42 & 58 for claims specified • California Certification (CDPH)

Filter Housing Dimensions: 18.5" Tall (includes 2.5" clearance for cartridge change) / 13.94" Wide / 4.38" Deep

Storage Tank Dimensions: 16.312" Tall / 9" Wide / 9" Deep

* System comes with a chrome airgap faucet (pictured). For additional faucet options, see our faucet guides on pg 52 & 53.

Reverse Osmosis systems require an airgap. See pages 96-97 for additional info.

3M RO401
Replacement Filters

Part # WI-3MROP411

Particulate Filter to be changed every 12 months

Part # WI-3MROP412

CTO Filter to be changed every 12 months

Part # WI-3MROP416

Cyst Filter to be changed every 12 months

Part # WI-3MROP413


TDS/Contaminant Filter to be changed every 36 months

REVERSE OSMOSIS SYSTEM ACCESSORIES FOR ALL OUR RO SYSTEMS



TDS Tester: Test your Total Dissolved Solids.

PART# WI-ENV-TDS-TESTER



AIRGAP: Wall Mounted.

PART# WI-RO-WALL-AIRGAP



AIRGAP: Multi-Purpose, for your RO system and 1 dishwasher, or a water softener.

PART# WI-COMBO-AG (plus your finish code)

MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.