



## MODEL DESCRIPTION

BG-3000 Water Filtration System Part # WI-BG3000

Shipping Wt: 5 lbs.



## LEVEL 2 Body Glove Water Filter System.

Featuring Tri Stage filtration and advanced protection from particles 0.5 micron in size and larger.

Includes a recyclable cartridge with an easy recycle program, and a filter change indicator.

FLOW RATE: 0.75 GPM

CAPACITY: 450 gallons or 1 year

**Dimensions:** W = 4.5" / D = 4.75" / H = 15.75"

(height includes 2.5" clearance for cartridge change purposes)

Enhance your water with an EverHot® Instant Hot System or EverCold® Water Chiller.



REDUCES: Chlorine Taste & Odor • Chloramines • \*\*Cloudiness, Sediment, Rust
Giardia Lamblia Cysts • Cryptosporidium Parvum Cysts • \*Molds and Algae\*\*\* • \*Lime Scale
Asbestos Fibers • \*\*Oxidized Iron • \*\*Oxidized Manganese • \*\*Oxidized Sulfides
0.5 Micron Particulate Reduction - Class 1 • Lead
Trihalomethanes (TTHMs) • Volatile Organic Chemicals (VOCs)

\*\*Based on Manufacturer's Data \*Contains KDF, a bacteriostatic and lime-scale control agent
\*\*\*Inhibits the sustained growth of Molds and Algae



System Tested and Certified by NSF International against NSF/ANSI Standards 42 and 53 in Model BG-3000 for the reduction of:

## Standard 42 - Aesthetic Effects

- Chemical Reduction
- Chlorine Taste & Odor
- Chloramines
- Mechanical Filtration
- Particulate Reduction- Class I

## Standard 53 - Health Effects

- Chemical Reduction
- Lead TTHM VOC Mechanical Filtration

BG-3000C Replacement Cartridge Part # WI-BG3000C

Shipping Wt: 3 lbs.



FLOW RATE: 0.75 GPM / CAPACITY: 450 gallons or 1 year


**EASY QUICK-CHANGE REPLACEMENT CARTRIDGE:** Body Glove Water Filter Systems have an automatic shut-off valve built into the head unit, so changing the cartridge is a breeze. Includes a filter change indicator.











MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. BEFORE installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.