



MODEL DESCRIPTION

HousePure® ScaleStop  
Whole House  
Commercial Grade  
Conditioner

Part # WI-HPSS-2  
**CHLORAMINE UPGRADE**  
Part # WI-HPSS-2-CHL



The HousePure ScaleStop 2 is the high capacity commercial version of the residential HousePure ScaleStop Conditioner. The HPSS 2 boasts 2" inlet and outlet lines for larger homes and businesses that require higher flow rates with the added scale control capacity. The pretreatment tank offers 4 cubic feet of premium coconut shell granular activated carbon along with 10 lbs of KDF-55 media. Together, these two mediums create a high degree of pretreatment benefits including dechlorination, bacteria inhibition, and taste and odor reduction. The second tank contains 88% more ScaleStop media than residential systems, ensuring that all water is properly treated for scale control.

The HPSS-2 has a 2" inlet and outlet, which can be bushed down to accept smaller pipe sizes if needed. The unit includes a 2900 series commercial, 24VDC controller and a 2" metered valve.

**Includes Installation Parts and Install/Owner's Manual**

**Dimensions (Including both tanks):** Width: 34" Height: 80" Depth: 32"

**Distance between tanks:** 2"

**Rough In Dimension:** 67" and 55"

**Flow Rate:** 30 GPM

**Pipe Size:** 2" inlet and outlet\*, 1" drain

**Media:** 4 cubic feet, coconut shell GAC (granular activated carbon) & 10 lbs, KDF-55  
+ 7.5-liters, ScaleStop resin

**CHL Upgrade Media:** 4 cubic feet, surface modified GAC & 10 lbs, KDF-55  
+ 7.5-liters, ScaleStop resin

**Operating Temp Range:** 34°F to 110°F (Not appropriate for freezing temperatures.)

**Water Pressure Range:** 20 PSI to 75 PSI

**Operating Voltage:** 24 VAC, 50/60 Hz, 120 VAC transformer included

**Water Quality:** Not for use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CA AB 1953 and VT Act 193.

**CUSTOMERS CONCERNED WITH CHLORAMINES CAN UPGRADE THIS PRODUCT.**

Our non-chemically impregnated coconut based activated carbon has been surface modified during manufacture. Our product is 3 times more effective than competitive products and 15 times more effective than our standard HousePure media.

**Upgrade to more complete chloramine removal! WI-HPSS-2-CHL**



**ESSENTIAL SCALESTOP INFO - PLEASE READ**

**This is not a water softener.** To assist you in your understanding of this product, you must read and sign the "Customer Expectation & Acknowledgment Form" before purchasing HousePure ScaleStop products. The customer's signed form must be provided with the dealer's purchase order. Thank you!  
**When installed in homes with new pipes, system MUST be in bypass mode for 120 days before use.**



**MAXIMUM recommended line pressure for this product is 75 PSI.** Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)