NOLF

PI363418

FEATURES

Breathe cleaner air and enjoy less greasy residue in your kitchen

Makes a statement with a bold, stainless, professional look

Adjust as needed with recessed controls that provide a sleeker look, yet maintain ultimate blower control

Matches the same heavy-duty stainless-steel construction, handfinished hemmed edges, and welded seams of all Sub-Zero, Wolf, and Cove products

Select from internal, in-line, or remote blower options (blower required)

Illuminates your cooking area with halogen lighting with two brightness settings

Rely on a heat sentry that automatically turns on the blower or increases its speed when exhaust temperatures exceed 200 degrees Fahrenheit

Minimizes the backward flow of cold air with backdraft transition

ACCESSORIES

Make-Up Air Damper

Inline Blowers

Internal Blowers

Remote Blowers

Pro Island Hood Duct Covers

Accessories available through an authorized dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.




BLOWER OPTIONS

- 300 CFM Internal
- 400 CFM Internal
- 600 CFM Internal
- 800 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- · 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote
- Dishwasher-safe Bassel filters
- · Halogen lighting

PRODUCT SPECIFICATIONS

Model	PI363418
Dimensions	36"W x 18"H x 34"D
Weight	95 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



 $\ensuremath{\operatorname{\textbf{NOTE:}}}$ Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS

