Woodford Utility Yard Hydrants are intended for irrigation purposes and designed for use where year-round availability of water is required. Sturdy construction make these hydrants rugged and dependable. Accidental damage and vandalism are minimized. Hydrants are available with choice of automatic close or manual close lever handle.

Freezeless **UTILITY Yard Hydrants** U34 / U75 3/4" FPT Inlet

WOODFORD

SUGGESTED USES:

Chemical plants; oil refineries; outdoor paved areas of schools, factories and office buildings; wading pools; outdoor ice rinks; stock and water tanks.

Features:

- Automatic draining occurs through 1/8" NPT drain hole when hydrant is shut off to prevent freezing.
- · Outlet can be located at any height above ground level. Adjust bury depth accordingly.
- All working parts are removable through the top of the hydrant.
- Lever handles can be easily removed to prevent unauthorized usage.

Specifications:

INLET: 3/4" FPT Brass Valve Body

OUTLET: Model U34: 3/4" Brass Hose Thd. Spout

Model U75: 3/4" FPT Galvanized Tee

HANDLES: Almag casting (see descriptions below)

(A) Automatic closing lever handle should be used in public places where supervision is inadequate to assure shut-off of water

(M) Manual closing lever handle should be installed where water is continuously used over a period of time.


OPERATING ROD: 1/4" galvanized pipe

CASING: 1" galvanized pipe MAX. PRESSURE: 125 PSI

SHIPPING WEIGHT

Bury Depth (Ft)	1	2	3	4	5	6	7
Weight U34 (lbs)	9	11	13	15	17	19	21
Weight U75 (lbs)	8	10	12	14	16	18	20












MODEL U34 & U75 PARTS LIST					
ITEM	PART#	DESCRIPTION			
1	41037	AUTOMATIC CLOSE HANDLE			
2	41025	MANUAL CLOSE HANDLE			
3	41201	SET SCREW			
4	41202	HANDLE PIN			
5	41029	PACKING NUT			
6	41014	O-RING			
7	41031	BONNET NUT (U34)			
8	50011	O-RING (U34)			
9	41036	SPOUT HEAD (U34)			
10	41021	VALVE BODY			
11	41043	BONNET NUT (U75)			
12	41632	STEM			
13	41239	1" X 1"X 3/4" HEAD (U75)			
14	41033	SPRING			
15	41631	COUPLING			
16	41624	LOCKNUT (2 REQD)			
17	U34 OPE	RATING ROD			
	42128	1 FT. BURY (25 ½" LONG)			
	42129	2 FT. BURY (37 ½" LONG)			
	42130	3 FT. BURY (49 ½" LONG)			
	42131	4 FT. BURY (61 ½" LONG)			
	42132	5 FT. BURY (73 ½" LONG)			
	42133	6 FT. BURY (85 ½" LONG)			
	42134	7 FT. BURY (97 ½" LONG)			
18	U75 OPE	RATING ROD			
	42125	1 FT. BURY (24 1/8" LONG)			
	42101	2 FT. BURY (36 1/8" LONG)			
	42102	3 FT. BURY (48 1/8" LONG)			
	42103	4 FT. BURY (60 1/8" LONG)			
	42104	5 FT. BURY (72 1/8" LONG)			
	42105	6 FT. BURY (84 1/8" LONG)			
	42106	7 FT. BURY (96 1/8" LONG)			
19	41013	SWIVEL SCREW			
20	41012	SWIVEL COUPLING			
21	41015	PLUNGER			
22	41014	O-RING (2 REQ'D)			
23	41016	FULLER BALL			
24	41017	FULLER BALL SCREW			
25	40040	BEARING WASHER			
	41018	PLUNGER REPAIR KIT (Includes Items 19-24)			



For more information contact...

WOODFORD MANUFACTURING COMPANY