


BOND

BLS32S

Bond Rally Series Wall Mounted Lavatory Faucet with Lever Handle



SHOWN IN BOND RALLY SERIES WALL MOUNTED LAVATORY FAUCET WITH LEVER HANDLE | BLS32S

TECHNICAL DETAILS

ADA Compliance: Yes
 Drain Depth Maximum: 2 5/8"
 Drain Depth Minimum: 3/8"
 Drain Hole Diameter: 1 3/4"
 Drain Style: Push Touch
 Fittings Hole Diameter: 1 3/8"
 Handle Turn Angle: Quarter Turn
 Inlet Connection Size: 1/2"
 Inlet Connection Type: Female NPT
 Number Of Holes: Two Hole
 Primary Material: Brass
 Restricted Maximum Flow Rate: 1.2 gpm
 Spout Swivel: N
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Modern designs infused with rare soul and artistry. Explore our wide range of Bond bath and kitchen elements, from fittings to fixtures to hardware.

CODES & STANDARDS

PRODUCT FEATURES

Lever Handle

Includes Universal Push-Touch Drain (UNLD23) which fits 1-1/2" through 1-3/4" drain hole openings

Features a Sport Black Finish, smooth and velvety to the touch

Stocked in Chrome/Sport Black

Available in 1.2gpm (4.5L/min) flow rate; Requires valve, sold separately: GULV29


CERTIFICATIONS

PRODUCT (NOTES)

BOND


BLS32S

Bond Rally Series Wall Mounted Lavatory Faucet with Lever Handle





TOP VIEW

SCALE: $\frac{1}{2}"=1'-0"$





ADAPTER INCLUDED - INTERNATIONAL USE ONLY



FRONT VIEW

SCALE: $\frac{1}{2}"=1'-0"$



SIDE VIEW

SCALE: $\frac{1}{2}"=1'-0"$