UNIVERSAL USHR15

Universal Recessed 15" Round Rain Showerhead with Circular Spray Pattern



TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed Spray Fittings Hole Diameter: 12" Inlet Connection Size: 1/2" Inlet Connection Type: Female Hose Pivot: N

Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN UNIVERSAL RECESSED 15" ROUND RAIN SHOWERHEAD WITH CIRCULAR SPRAY PATTERN | USHR15

INSPIRATION CODES & STANDARDS

Our Universal collection features timeless designs complementing any of our Waterworks. With a wide range of product, from fittings to accessories, Universal adds exquisite proportion and balance to any environment.

PRODUCT FEATURES

Made of Brass

15" ceiling mounted rain showerhead

Easy clean rubber nozzles prevent calcium buildup

Stocked in Brass, Chrome and Nickel

Showerhead available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS

PRODUCT (NOTES)

UNIVERSAL USHR15

Universal Recessed 15" Round Rain Showerhead with Circular Spray Pattern

