Engineering Specification

| Job Name | Contractor |
|--------------|-----------------------|
| Job Location | Approval |
| Engineer | Contractor's P.O. No. |
| Approval | Representative |
| Тад | |

QT-101-D-BF Pat. No. 10,895,070 QT QuickTurn™ Back-To-Back Horizontal Carrier for Floor Mounted Back Outlet Bowl 16 1/4" Min. 26 1/4" Max.

Specification

Watts QT-101-D-BF back-to-back horizontal water closet carrier for floor mounted back outlet bowl with epoxy coated cast iron fitting, 4"(102) no hub waste and 2"(51) no hub vent connections, epoxy coated cast iron patented faceplate assembly, epoxy coated cast iron foot supports with incremental height markings, and adjustable ABS nipple with integral test cap and neoprene bowl gasket, plated hardware and chrome cap nuts.

| Options Suffix Description | | | |
|-------------------------------|--------------------------|--|---|
| -3 | 3" No Hub Fitting | | |
| -36 | 36" Long Barrel Fitting | | |
| -HS | Hub & Spigot Connections | | |
| -M1 | ABS 24" Extended Nipple | | - |

NOTICE

Anchor legs to concrete floor with minimum 1/2"(13) anchor bolts (by others).

Carrier feet require one 1/2"(13) anchor bolt per foot.

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

2"(51) Vent 16 1/4" Min. 26 1/4" Max. 9 1/4" (236)5 3/8" 1 3/4" (137) (44) 1" Min. 2" 6" Max. (51) 5/16' 6 5/8' (8) (168) 2 3/4 10 1/4" (70) (260) 17 3/4" (451)18 3/8" (467) ο 9' (229)6 (162)3/4" 5 3/8" (45)(137)17 3/4" (451) (102) 1/4"-3" Min. (32)1/2"(13) 4 1/2" Max. 13/16Tapped Hole (30)

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (800) 338-2581 • F: (828) 248-3929 • Watts.com Canada: T: (888) 208-8927 • F: (888) 479-2887 • Watts.ca Latin America: T: (52) 55-4122-0138 • Watts.com