#### **Engineering Specification**

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

Pat. No. 10,895,070

# **QT-101-L/R-BF**

### QT QuickTurn™

#### Single Horizontal Carrier for Floor Mounted Back Outlet Bowl Specification

Watts QT-101-L/R-BF single horizontal water closet carrier for floor mounted back outlet bowl with epoxy coated cast iron fitting, 4"(102) no hub waste and 2"(51) no hub vent connections, epoxy coated cast iron patented faceplate assembly, epoxy coated cast iron foot supports with incremental height markings, and adjustable ABS nipple with integral test cap and neoprene bowl gasket, plated hardware and chrome cap nuts.

Suffix	Options Description	
-3	3" No Hub Fitting	112
-36	36" Long Barrel Fitting	S Same
-HS	<b>Hub &amp; Spigot Connections</b>	
-M1	ABS 24" Extended Nipple	Camon




## NOTICE


Anchor legs to concrete floor with minimum 1/2"(13) anchor bolts (by others).

Carrier feet require one 1/2"(13) anchor bolt per foot.

#### NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.





Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



© 2021 Watts

ES-WD-QT-101-L/R -BF 2127