

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:
www.zoeller.com

A-PAK ALARM SYSTEMS

The "A-Pak" Alarm system sounds a horn when a potentially threatening liquid level condition occurs. The horn can be silenced, but the alarm light remains on until the condition is remedied. Once the condition is cleared, the alarm will automatically reset.

A green "POWER ON" light indicates 120V primary power to the alarm. A low battery chirp feature indicates when the battery should be replaced. A red "ALARM" light indicates a high-level condition.

10-1494 "A-PAK" Alarm

- NEMA 1 enclosure (INDOOR USE ONLY)
- Automatic alarm reset
- Horn is rated 87 decibels at 10'
- 9V battery back-up (battery not included)
- 15' alarm (12V) tethered switch
- 6' power cord
- Auxiliary dry contacts (use P/N 10-2614)
- UL / CSA listed

10-2613 "A-PAK" Alarm

Same standard features of our 10-1494 with:

- 15' alarm (12V) alarm reed switch
- Auxiliary dry contacts (use P/N 10-2615)

NOTE: It is always recommended to power the alarm from a separate circuit than the pump to avoid losing power to both during a tripped breaker scenario.

Models 10-1494



Tested to UL Standard
UL 508
& Certified to CSA
Standard
C22.2 No. 205

Models 10-2613



Tested to UL Standard
UL 508
& Certified to CSA
Standard
C22.2 No. 205



Model 10-0623

Tested to UL Standard UL 508
& Certified to CSA Standard
C22.2 No. 205

10-0623 INDOOR / OUTDOOR Alarm System

- NEMA 3R enclosure (6.5" X 4.5" X 3")
- Automatic alarm reset, horn silence switch and alarm test switch
- Horn is rated 85 decibels at 10'
- Pre-mounted terminal block with connections for pump and float switch
- 15' alarm (12V) tethered switch
- Power connections are field wired
- UL / CSA listed



Model 10-0126

UL US LISTED

10-0682 DELUXE Alarm System includes same features of our 10-0623 with:

- 20' alarm (12V) tethered switch
- 6' 115V power cord with water-tight cord connectors

10-0126 INDOOR / OUTDOOR Alarm System includes same features of our 10-0623 with:

- NEMA 4X thermoplastic enclosure (6" X 4" X 3")
- Horn is rated 88 decibels at 10'
- 5A auxiliary dry contacts
- UL Listed to Canadian standard cULus

10-2616 Auto-Dialer System

The Auto-Dialer is a single channel voice dialer that can be used with any device that can provide a normally open / closed contact. It can be programmed to store up to four numbers to dial, including standard (voice) telephones, most cellular phones, and pagers. It will provide a 16 second pre-recorded message.

- Voice-Chip technology (NO TAPES)
- Record your own personal messages
- Dials each contact number up to four times
- Internal 9V battery back-up (Battery NOT Included)
- Tone or pulse dial only (NOT intended for digital phone lines)

Model 10-2616 Auto Dialer

