



Zurn PEX® CR - Polymer Fittings


UL 1821 Listed Barb x MPT Adapter - QQPMC55FX

Specification Sheet

Tag _____

Dimensional Data: Inches and [mm] are subject to manufacturing tolerances and change without notice.

Note: Barb geometry will vary depending upon barb size.



Part	Description	'A'	'B'	'C'
QQPMC55FX	1" Barb x 1" MPT Adapter	1" Barb	1" - 14 NPT	2.21" [56.1]

Engineering Specification: Zurn PEX® CR Polymer Male Adapter.

The QQPMC55FX adapter is used to transition from female pipe thread to PEX tubing. Molded from Acudel®. These fittings, as a system with Zurn PEX® tube, are pressure rated at 160 PSI at 73°F, 130 PSI at 120°F (fire protection rating), 100 PSI at 180°F, and 80 PSI at 200°F. These fittings are listed by NSF as complying with the following standards: NSF/ANSI Standard 14, NSF/ANSI Standard 61, ASTM F877, CSA B137.5, ASTM F2159, and UL 1821.

Accessories

- ___ **QCLP5X** 1" QuickClamp® Crimp Ring
- ___ **QCR5X** 1" Copper Crimp Ring

Rev.	Date: 010/8/10	C.N. No. 111811
Dwg. No. 302752		Prod. No. QQPMC55FX